

RUUD[®] SALES FACT SHEET



ACHIEVER[®] Series

UAND- SERIES

Seven Models

13 SEER Models

With efficiencies up to 14.45 SEER
in certain matched systems.

Nominal Sizes 1 1/2 to 5 Tons
[5.28 kW] to [17.6 kW]

Cooling Capacities

16,800 to 56,000 BTU/HR
[4.92 kW] to [16.41 kW]

GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Condenser Coil leaks caused by	
factory defectsFive (5) Years
Compressor	
A-SeriesEight (8) Years
B-SeriesSeven (7) Years
*Any Other PartFive (5) Years

*This five year limited warranty is applicable only to single-phase products installed in residential applications on or after January 1, 2001.

Features


The *Ruud Achiever Series*[®] High Efficiency UAND- Condensing Unit was designed with performance in mind. These units offer comfort, energy conservation and dependability for single, multi-family and light commercial applications.

- Attractive, louvered wrap-around jacket protects the coil from yard hazards and weather extremes. Top grille is steel reinforced for extra strength. Cabinet is powder painted for all-weather protection.
- Air is discharged upward away from bushes and shrubs. The discharge pattern of the top grille provides minimum air restriction, resulting in quiet fan operation.
- Exclusive Combination Grille/Motor Mount secures the motor to the underside of the discharge grille. The grille protects the motor windings and bearings from rain and snow.
- All controls are accessible by removing one service panel. Removable top grille provides access to the condenser fan motor and condenser coil.
- Single speed motor designed for low speed, quiet, energy-saving operation.
- All models meet or exceed a 1000-hour salt spray test per ASTM B117 Standard Practice for Operating Salt Spray Testing Apparatus.

<u>U</u>	<u>A</u>	<u>N</u>	<u>D</u>	<u>—</u>	<u>024</u>	<u>J</u>	<u>A</u>	<u>Z</u>
RUUD	REMOTE CONDENSING UNIT	HI-EFFICIENCY (STANDARD)	DESIGN SERIES		COOLING CAPACITY	ELECTRICAL DESIGNATION	VARIATIONS	COOLING CONNECTION FITTING
			D = FOURTH DESIGN		018 = 18,000 BTU/HR [5.28 kW] 024 = 24,000 BTU/HR [7.03 kW] 030 = 30,000 BTU/HR [8.79 kW] 036 = 36,000 BTU/HR [10.55 kW] 042 = 42,000 BTU/HR [12.31 kW] 048 = 48,000 BTU/HR [14.07 kW] 060 = 60,000 BTU/HR [17.58 kW]	J = 208/230V-1-60 C = 208/230V-3-60 D = 460V-3-60 Y = 575V-3-60	A-SERIES = FULL FEATURE B-SERIES = COMPETITIVE	Z = SWEAT W/SCROLL

[] Designates Metric Conversions

Price	Starting at: \$
-------	--------------------



"CERTIFIED UNDER THE A.R.I.
CERTIFICATION PROGRAM—
A.R.I. STANDARD 210"