



DIRECT VENT WALL FURNACE



S21 LINE

SPECIAL MODELS ADAPTED
TO THE STANDARDS
ANSI Z21.86-2004
AND CSA 2.32-2004

Electricity not required.
can be used as emergency heat
during power outages.

PRODUCT
OF ESKABE S.A.

eskabe

Specialists in Heating.

SPECIFICATIONS	DVEL 8	DVEL 12	DVEL 20
Power Input (KW)	2,32	3,20	4,94
Power Input (Btu/h)	8000	11000	17000
Thermostat	No	Yes	Yes
Fuel	Natural Gas or LPG / Propane	Natural Gas or LPG / Propane	Natural Gas or LPG / Propane
Shipping Weight	12,1 kg* 26,7 lb*	16,0 kg* 35,3 lb*	24,0 kg* 52,9 lb*

*(Venting kit & carton included)

DIMENSIONS

Cabinet Height	50,8 cm 20 in	50,8 cm 20 in	50,8 cm 20 in
Cabinet Width	34,6 cm 13 5/8 in	44,1 cm 17 3/8 in	69,5 cm 27 3/8 in
Cabinet Depth	14,1 cm 5 9/16 in	14,8 cm 5 13/16 in	16,6 cm 6 9/16 in
Vent Opening Required	12,7 cm 5 in	15,2 cm 6 in	17,8 cm 7 in


STANDARD HEATING SPACE

Heated Area	200 ft ² 18.6 m ²	275 ft ² 25.6 m ²	425 ft ² 39.5 m ²
-------------	--	--	--

GAS CONSUMPTION

Natural Gas	7.44 ft ³ /h	10.23 ft ³ /h	15.81 ft ³ /h
LP Propane	3.2 ft ³ /h	4.4 ft ³ /h	6.8 ft ³ /h

USE SITUATION



NOTE

For installation purposes it is necessary to consider the depth added by the hanging bracket - 2 1/32 in - (5,2 cm)

To enable constant quality improvement, ESKABE reserves the right to change any design specification without notice.



ESKABE S.A.

ISO 9001:2000 IRAM-RI 9000-365

www.eskabeusa.com

HEADQUARTERS
Dr. Nicolás Repetto 1545 (C1416CLI)
C. A. de Buenos Aires
Tel: (54 11) 4581-4119
Fax: (54 11) 4583-1880

ESKABE USA DISTRIBUTOR
JOHN J. SQUIRES
494 Dixon Road
Friendsville, MD USA 21531
Tel: 301-616-7549
Fax: 775-640-2355
Tollfree: 888-395-1164 USA